

ENSERVER 50KWH

TECHNICAL DATE SHEET



TECHNICAL DATA SHEET

ENSERVER 50kWh 48V

PERFORMANCE SPECIFICATIONS

MODEL	50 KW
Noise(dB)	≤45 dB
Communication with BMS	RS485; CAN
Cooling	Intelligent air cooling

BATTERY INPUT DATA

Battery Voltage Range(V)	160~800
Max. Charging Current(A)	100A
Max. Discharging Current(A)	100A
Number of Battery Input	2
Charging Strategy for Battery	Self-adaption to BMS

PV INPUT

Max. DC Input Power(W)	65000
Max. DC Input Voltage (V)	1000
MPPT Range(V)	180
Start-up Voltage(V)	150-850
Full Load DC Voltage Range (V)	450-850
Rated DC Input Voltage (V)	600
PV Input Current(A)	144
Max.PV Isc(A)	220
No. of MPPT Trackers	4

TECHNICAL DATA SHEET

ENSERVER 50kWh

AC OUTPUT DATA

Rated AC Output and UPS Power(W)	50000
Max. AC Output Power(W)	55000
Peak Power(off grid)	1.5 time of rated power, 10 S
AC Output Rated Current(A)	75.8/72.5
Max. AC Current(A)	83.4/79.8
Max. Three-phase Unbalanced Output Current A	83.3
Max. Continuous AC Pass through(A)	150
Power Factor	0.8 leading to 0.8 lagging
Output Frequency and Voltage	50/60Hz; 3L/N/PE 220/380, 230/400Vac
Grid Type	Three Phase
DC injection current (mA)	<0.5%1n

EFFICIENCY

Max. Efficiency	97.60%
Euro Efficiency	97.00%
MPPT Efficiency	>99%

PROTECTION

PV Input Lightning Protection	Integrated
Anti-islanding Protection	Integrated
PV Input Lightning Protection	Integrated
Insulation Resistor Detection	Integrated
Residual Current Monitoring Unit	Integrated

TECHNICAL DATA SHEET

ENSERVER 50kWh 48V

Output Over Current Protection	Integrated
Output Shorted Protection	Integrated
Output Over Voltage Protection	DC Type II / AC Type III
Battery Over Current Protection	Fuses
MECHANICAL DIMENSIONS	
Size(mm)	527W×894H×294D
Weight(kg)	75
Installation Style	Wall-mounted